



مكينة ربط الحديد الكهربائية

Pwer Re Bar -Tier

Specifications	Model No.		
	ME-RT280	ME-RT450	ME-RT 580
Max Tying Diameter Rebar	4 - 30 mm	8 - 42 mm	12 - 62 mm
Ties per charger	3300 Knots	2700 Knots	2500 Knots
Wraps per knot	2-3 wraps	2-3 wraps	3-4 wraps
Wire diameter	0.8mm	0.8mm	0.8mm
Length of per coil	100m	100m	100m
Net weight	2.7Kg	2.7Kg	2.8Kg
Package Size	48.5x13.5x38.5cm	48.5x13.5x38.5cm	48.5x13.5x38.5cm
Package weight	7.65 Kg	7.65 Kg	7.70 Kg
Weight per coil	0.40Kg	0.40Kg	0.40Kg
Ties per roll of wire	230-170 Knots	170-120 Knots	90-78 Knots
Battery pack per unit	2PCS	2PCS	2PCS
Battery charger per unit	1 PCS	1 PCS	1 PCS

Specifications

Reduces Tying Time

About 5 times faster than manual tying. Makes ties in less than 1 sec. per tie with consistent tie strength. High speed tying saves you time and money.

Delivery Time - within 10 work Days

2 Page